

PRODUCT INFORMATION


APPLICATION

Wiring all types of sound systems
 Wiring in fixed and mobile installations
 Identification of wires by colors (Red/Black) (Diagram 1)
 or mechanical indexing by grooves (Diagram 2)

FEATURES



Operating temperature:
 Fixed point: -25°C → +70°C
 Mobile station: -5°C → +70°C



Minimum bending radius:
 8 x Ø



In accordance with the RoHS directive

ELECTRICAL PROPERTIES

Maximum stress:	300 V
Resistance of the soul at 20°C:	
0.50 mm ² :	61,9 Ω/km
0.75 mm ² :	36.1 Ω/km
1.0 mm ² :	27.1 Ω/km
1.5 mm ² :	18,1 Ω/km

PRODUCT REFERENCES

			Diagram	Colors
CHPM2X075 N , G or BL	2 × 0,75	2,1 × 4,2	2	Black, Gray, or White
CHPM2X0.75 RN	2 × 0,75	2,1 × 4,2	1	Red / Black
CHPM2X1 G	2 × 1,0	2,4 × 4,8	2	Gray
CHPM2X1 RN	2 × 1,0	2,4 × 4,8	1	Red / Black
CHPM2X15 RN	2 × 1,5	2,6 × 5,2	1	Red / Black