

# H05 / 07V-U

Single-core wiring cable, V-U



**Conductor:**  
Red single-core copper  
Class 1 according to: IEC 60228

**Isolation:**  
PVC type Tl1  
Color: blue, brown, white, gray, brown, black, orange, red, purple, green/yellow



FT 115/03/2016 EN

## PRODUCT INFORMATION

### APPLICATION

The harmonized H05/07V-U cables are equipped of a PVC duct for fixed installation.

### ELECTRICAL PROPERTIES

Rated voltage U <sup>o</sup> /U:	
- H05	300 / 500V
- H07	450 / 750V

### FEATURES



Fire resistance:  
EN 60332-1



Service temperature:  
-5°C → +70°C  
Minimum installation temperature: +5°C







Minimum radius of curvature:  
6 x Ø



In accordance with the RoHS directive

Reference standards  
EN 50525-2-31

**PRODUCT REFERENCES**

			
<b>H05V-U</b>			
VU050	0,50	2.3	9
VU075	0,75	2.5	12
VU1	1	2.7	14
<b>H07V-U</b>			
VU15	1,50	3.2	12.1
VU25	2,50	3.9	7.41
VU4	4	4.4	4.61
VU6	6	5.0	3.08
VU10	10	6.4	1.83